

**IN THE CLAIMS:**

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with strikethrough. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please CANCEL claim 14 and AMEND the claims in accordance with the following:

1. (currently amended) A computer-readable medium storing a program for displaying a radar chart on the screen of a display unit, the program causing a computer to ~~perform the processes of execute~~:

judging a degree of association between each of a plurality of axial labels and at least one arranged keyword on the basis of data indicative of the relationship between each of the plurality of axial labels and the arranged keyword;

assigning the plurality of axial labels to a plurality of axes on a radar chart and setting a reference point for the assigned axial label on each of the plurality of axes;

setting a display position for the arranged keyword at a location nearer to a reference point for an axial label the degree of association of which with the arranged keyword is relatively high than to a reference point for an axial label the degree of association of which with the arranged keyword is relatively low; and

displaying an image indicative of the arranged keyword at the display position set on the radar chart.

2. (currently amended) The ~~program~~ computer-readable medium according to claim 1, wherein a line segment which connects the image indicative of the arranged keyword and a reference point for each of the plurality of axial labels is displayed in a thickness corresponding to a degree of association between the arranged keyword and each of the plurality of axial labels.

3. (currently amended) The computer-readable medium ~~program~~ according to claim 1, wherein if there are a plurality of arranged keywords, an image indicative of each of the plurality of arranged keywords is displayed on one radar chart.

4. (currently amended) The computer-readable medium ~~program~~ according to claim 3, further causing a computer to ~~perform the process of execute~~ remaking a radar chart on which only a selected image is to be displayed in response to operation input for selecting the image provided while the radar chart on which the images indicative of the plurality of arranged keywords are shown is being displayed.

5. (currently amended) The computer-readable medium ~~program~~ according to claim 4, wherein if a radar chart on which only the selected image is to be displayed is remade, a broken line indicative of the characteristics of an arranged keyword indicated by the selected image is displayed on the newly made radar chart.

6. (currently amended) The computer-readable medium ~~program~~ according to claim 1, further causing a computer to ~~perform the process of execute~~ remaking a radar chart on which the axial labels have been replaced with the arranged keywords and on which the arranged keywords have been replaced with the axial labels by the use of original tabular data for the radar chart being displayed in response to operation input provided while the radar chart is being displayed.

7. (ORIGINAL) The computer-readable medium ~~program~~ according to claim 1, wherein a virtual spring force which changes according to distance is defined between a display position for the arranged keyword and a reference point for an axial label to which the arranged keyword has a relationship, further wherein a location where all the spring forces acting at the display position for the arranged keyword are balanced is set as a display position for the arranged keyword.

8. (currently amended) The computer-readable medium ~~program~~ according to claim 7, wherein as the degree of association between the arranged keyword and the axial label increases, the spring force becomes stronger.

9. (currently amended) The computer-readable medium ~~program~~ according to claim 7, wherein a virtual repellent force is defined between the display position for the arranged keyword and a reference point for an axial label to which the arranged keyword has no relationship, further wherein a location where all the spring and repellent forces acting at the position for the arranged keyword are balanced is set as a display position for the arranged

keyword.

10. (currently amended) The computer-readable medium ~~program~~ according to claim 1, further causing a computer to ~~perform the processes of~~execute:

extracting keywords included in a plurality of pieces of text data and calculating the degree of association between the extracted keywords; and

judging a degree of association between each of axial labels and an arranged keyword by specifying the axial labels and the arranged keyword from among the extracted keywords.

11. (currently amended) The computer-readable medium ~~program~~ according to claim 1, further causing a computer to ~~perform the process of~~execute generating data from which the contents of a displayed radar chart can be reproduced and outputting the generated data in response to operation input.

12. (ORIGINAL) A method for displaying a radar chart on a computer screen, the method comprising the steps of:

judging a degree of association between each of a plurality of axial labels and at least one arranged keyword on the basis of data indicative of the relationship between each of the plurality of axial labels and the arranged keyword;

assigning the plurality of axial labels to a plurality of axes on a radar chart and setting a reference point for the assigned axial label on each of the plurality of axes;

setting a display position for the arranged keyword at a location nearer to a reference point for an axial label the degree of association of which with the arranged keyword is relatively high than to a reference point for an axial label the degree of association of which with the arranged keyword is relatively low; and

displaying an image indicative of the arranged keyword at the display position set on the radar chart.

13. (currently amended) ~~A radar chart display control unit for~~ An apparatus displaying a radar chart on a screen, ~~the unit~~said apparatus comprising:

a controller,

~~a degree of association judgment section for~~ judging a degree of association between each of a plurality of axial labels and at least one arranged keyword on the basis of data indicative of the relationship between each of the plurality of axial labels

and the arranged keyword;

~~a reference point setting section for assigning the plurality of axial labels to a plurality of axes on a radar chart and for setting a reference point for the assigned axial label on each of the plurality of axes;~~

~~a display position setting section for setting a display position for the arranged keyword at a location nearer to a reference point for an axial label the degree of association of which is judged by the degree of association judgment section to be relatively high than to a reference point for an axial label the degree of association of which is judged by the degree of association judgment section to be relatively low; and~~

~~a display section for screen displaying an image indicative of the arranged keyword at the set display position set by the display position setting section.~~

14. (CANCELLED)